

PRODUCT SUBMITTAL

SGMH-882



APPLICATION

The Matterhorn 882 ionization system is intended to be mounted in the supply duct or air handler of a heating, cooling, or ventilating system. The unit is intended to operate only when air flow is present, thus, power to the ionization unit should be interlocked with fan operation, or controlled via an air pressure switch. The size and number of ionization systems is dependent upon the airflow, size of the space, and severity of the pollution and odors. Ionization can be adjusted with a knob.

Optional/Available:

- Air Switch
- Mounting Bracket
- Timer
- Remote Monitoring Panel

Figure 1

	Tube Size	Tube Number	Flowrate (CMH)	mm of WG	Pascals Pa	Steady State mA
M-882	C	(2)	3,400	0.2032mm	2.00	34.00
	D	(2)	5,100	0.6121mm	6.00	35.00
	E	(2)	6,800	1.2243mm	12.00	35.00
	F	(2)	8,500	1.7348mm	17.00	37.00



SPECIFICATIONS

General Product Information

Air Flow Rating	Up to 8,500 CMH
Pressure Drop	Minimal
Housing Material	Flame-Rated, High Impact ABS
Weight	2.83 kg
Max Operation Temp.	65.6°C

Electrical

Rated Voltage	220 or 250 VAC
Frequency	50/60 Hz
Power Consumption	6 Watts
Current Draw	0.4 Amps
Fuse	1.25 Amp 220 VAC 1.0 Amp 250 VAC
Field Electrical Connection	Field Electrical Connection; 3-Wire to Jct. Box or Country Specific Cord-Set

Ionization Tube

Material	Multi-Core Composite
Max Quantity	Two (2)
Compatible Tube Sizes	C (177.8mm) D (243.8mm) E (355.6mm) F (558.8mm)
Estimated Tube Life	17,600 Hours (Two Years)

Dimensions

See Figure 2 for more details

Approvals

CE and Intertek ETL to UL Standards: 2998, 1995, 867, 867A; CSA 22.2 Zero Ozone Emissions, Heating & Cooling Equipment, Electrostatic Air Cleaners, Commercial/Industrial Indoor Air Quality Systems.

